



PT-360-27

27x Zoom Outdoor Day/Night PTZ Camera



-Features-

- Fast and Silent Motion
- Endless 360° Pan Rotation
- 27x Optical, 12x Digital
- 127 Presets with Labels
- Fan & Blower
- Image Stabilization



Options:

- | | |
|----------------------|----------------------|
| Bracket: | Adaptor: |
| • PTWM-200 (wall) | • PTCRM-200 (corner) |
| • PTCM-200 (ceiling) | • PTPM-200 (pole) |

-Specifications-

PT-360-27	
Sensor	1/4" Sony Super HAD
Resolution	550 TV Lines / 680 TV Lines
S/N Ratio	50dB (AGC Off)
Focal Length	f=3.5 ~ 94.5mm / F1.6 ~2.9
Zoom Speed	1.8sec (Wide to Tele)
Min. Illumination	0.4 Lux (Color) / 0.02 Lux (B/W)
Day & Night	Auto / Day / Night (IR Cut Filter)
Focus	Auto / Manual / Semi-Auto
Iris	Auto / Manual
Shutter Speed	256 ~ 1/120,000 sec
Auto Gain Control	Low / Middle / High / Off
White Balance	Auto / Manual
Back Light Compensation	BLC / HLC / Off
Flickerless	Selectable
SSNR	Low / Middle / High / Off
Privacy Mask	8 Masks with Spherical Coord's
Range	On / Off
Pan/Tilt Speed	Preset: 360°/sec, Manual: 0.05° ~360°/sec, Swing: 1°~180° sec
Pattern	4 Patterns
Swing	8 Swings
Group	8 Groups
Other Functions	Auto Flip, Auto Parking, Power-up Action
Communication	RS-485
Protocol	Pelco-D, Pelco-P Selectable
Dimensions	7.6(D) x 7.5(H) Inches
Weight	6.6lbs without bracket
Power	AC 24V
Material	Poly Carbonate & Aluminum
Fan & Heater	F: Always, H: below 50°F (10°C)
Operating Temp	32° ~ 104°F (0°~40°C)