



PT-540-36

Auto Tracking PTZ Dome Camera



-Features-

- Motion Tracking Function
- Outdoor Weather-Resistant
- 36x Optical, 12x Digital
- Vandal Resistant Case & Cover
- Day & Night
- 128 Presets
- Pattern Function



-Specifications-

PT-370-36	
Sensor	1/4" Sony Ex View CCD
Resolution	540 TV Lines
Viewing Angle	57.8° (wide) / 1.7° (tele)
Zoom	36x Optical / 12x Digital
Illumination	1.4 Lux / 0.01 Lux
Focus	Auto / Manual
White Balance	Auto / Manual (ATW, Indoor, Outdoor, One Push WB, Manual WB) / Wide Dynamic Function
Shutter Speed	1/3 ~ 1/10,000 sec
Iris Control	Auto / Manual / Auto Slow Shutter
Gain Control	Auto / Manual
Video Output	1.0 Vp-p, Y/C Output
S/N Ratio	More than 50dB
PTZ Characteristics	360° PAN (0.4°~320° per sec) / 90° Tilt (0.4°~150° per sec) with Auto Flip / Vario-Speed Control, Proportional & Constant PT Speed
On Screen Display	Date / Time / Zoom / Temp
Object Tracking	Manual Activation / Preset Triggering / Scheduled Activation / Tracking Zone Selection
Communication	RS-485, 16 Multiple protocol
Auto Pan	Yes, Between 2 Presets
Tour/Sequence	4 Prog tours with Max 32 presets / 4 Patterns up to 180s
Alarm Inputs	7 inputs / 2outputs
Power	24V AC, 48W
Operating Temp	-40° ~ 140° F (-40° ~ 60° C)